



Selected LED luminaires for standard applications

- Energy savings up to 85 %¹
- Direct replacement for standard luminaires possible in most cases
- Simple mounting and connection
- Reliable quality from the lighting specialists at OSRAM
- Up to five years' guarantee on all luminaires in the Essentials product range²
- Optimum price-performance ratio

¹ Compared to luminaires with standard technology
² www.osram.com/professional-guarantee

Light is simple

Essentials LED luminaires

LED solutions for any lighting task.

Light is **OSRAM**

sITeCO
AN OSRAM BUSINESS

OSRAM

Finding the best solution: Essentials LED luminaires

How can you help your customers optimise their quality of light and at the same time lower their operating costs for the long-term? OSRAM is constantly working to support you in all professional areas of application with innovative lighting solutions.

OSRAM ensures that modern light is possible virtually anywhere with attractive LED luminaires for important standard applications – and offers you valuable input for your successful lighting business. Every one of these luminaires is extremely impressive as a result of its exemplary efficiency, long life, proven OSRAM quality, and really easy installation.

Benefit from our essential response to the demands of your customers - and take advantage of our shared experience regarding innovative lighting technology, consulting, logistics and service.



Downlights



Recessed luminaires



Wall and ceiling luminaires



Batten luminaires



Damp-proof luminaires



Outdoor



PUNCTOLED® I

- Compact downlight replacement for conventional halogen products
- Dimmable and with 25° swivel angle
- Recommended for hallways, stairs, and dressing rooms

SAVES UP TO 80% ENERGY*



PUNCTOLED® II

- Dimmable LED downlight with diffused, uniform light
- Recommended for hallways, stairs, and side-rooms

SAVES UP TO 40% ENERGY*



PUNCTOLED® IP65

- LED downlight with extremely shallow housing for a reduced installation depth
- Recommended for side-rooms, bathrooms, porches (outdoors)

SAVES UP TO 80% ENERGY*



OSRAM DEDRA plus® LED

- Economical LED recessed luminaire with opal cover for soft harmonious light
- Recommended for offices, conference rooms, waiting rooms, hallways

SAVES UP TO 45% ENERGY*



DIADEM® LED

- Ultra-thin recessed LED ceiling luminaire with pendant accessories kit
- Ideal replacement for traditional louvre luminaires
- Recommended for hallways, walkways, and conference rooms

SAVES UP TO **38 %** ENERGY¹



LED RONDEL

- High-value wall and ceiling luminaire with or without integrated high-frequency sensor
- Includes additional indirect lighting
- Recommended for hallways, hobby rooms and bathrooms

SAVES UP TO **65 %** ENERGY¹



POSIVO® LED

- LED wall and ceiling luminaire for uniform illumination
- Available with or without sensor
- Recommended for stairs, hallways and foyers

SAVES UP TO **65 %** ENERGY¹



LUMILUX® Combi LED

- Can be used as a linear LED strip lighting or as an individual luminaire
- Recommended for hallways, entrances, basements and for shelf-mounting

SAVES UP TO **45 %** ENERGY¹



NEPTUNE® LED

- Functional damp-proof luminaire (water-jet protected to IP 65)
- Recommended for industrial and warehouse areas, parking lots, garages, passageways and workshops


SAVES UP TO **51 %** ENERGY¹



NOXLITE® LED HP Floodlight

- High-power LED spotlight with adjustable sensors and IP44 protection rating
- Adjustable sensors for optimum security
- Recommended for driveways, garages

SAVES UP TO **84 %** ENERGY¹



AquaLED® 2 S, M












- LED pathway lighting with high quality of light and low glare due to uniform, diffused light distribution
- Recommended for pathways, patios

SAVES UP TO **85 %** ENERGY¹

¹ Compared to luminaires with standard technologies. The possible power loss of traditional control gear solutions is part of the calculation of the anticipated energy savings

OSRAM Essentials LED luminaires

Technical data at a glance.

Order code (EAN)	Article description	lm	W	K	t ₉₀ ²
PUNCTOLED® I					
 4008321999320	PUNCTOLED® I 2×4,5W	2 × 200	9	3.000	up to 25.000
4008321999344	PUNCTOLED® I 2×8,5W	2 × 450	17	3.000	up to 25.000
4008321999368	PUNCTOLED® I 10,5W	625	10.5	3.000	up to 25.000
PUNCTOLED® II					
 4052899904088	PUNCTOLED® II 10W	600	10	3.000	up to 50.000
4052899904095	PUNCTOLED® II 15W	1.000	15	3.000	up to 50.000
4052899904101	PUNCTOLED® II 20W	1.450	20	3.000	up to 50.000
PUNCTOLED® IP65					
 4052899910645	PUNCTOLED® IP65 2×5,5W	2 × 330	11	3.000	up to 50.000
4052899910652	PUNCTOLED® IP65 10W	600	10	3.000	up to 50.000
OSRAM DEDRA plus® LED					
 4052899920941	OSRAM DEDRA plus® LED 600×600	2.700	30	4.000	up to 30.000
4052899920934	OSRAM DEDRA plus® LED 600×600	3.600	40	4.000	up to 30.000
4052899920972	OSRAM DEDRA plus® LED 1200×300	3.600	40	4.000	up to 30.000
DIADEM LED³					
 4052899925830	DIADEM LED 600×600	ca. 3.000 ¹	ca. 35 ¹	4.000	up to 35.000
4052899925861	DIADEM LED 1200×300	ca. 4.000 ¹	ca. 47 ¹	4.000	up to 35.000
LED RONDEL					
 4052899908635	LED RONDEL	1.000	20	3.000	up to 30.000
4052899910195	LED RONDEL with Sensor	1.000	20	3.000	up to 30.000
POSIVO® LED					
 4008321854629	POSIVO® LED	800	17	3.000	up to 35.000
4008321854643	POSIVO® LED with Sensor	800	17	3.000	up to 35.000
LUMILUX® Combi LED					
 4052899909298	LUMILUX® Combi LED 10W	850	10	3.000	up to 35.000
4052899909304	LUMILUX® Combi LED 10W	950	10	4.000	up to 35.000
4052899909311	LUMILUX® Combi LED 18W	1.650	18	3.000	up to 35.000
4052899909328	LUMILUX® Combi LED 18W	1.780	18	4.000	up to 35.000
NEPTUNE® LED					
 4052899910560	NEPTUNE® LED small	2.000	25	4.000	up to 50.000
4052899910577	NEPTUNE® LED medium	4.000	50	4.000	up to 50.000
NOXLITE® LED HP Floodlight					
 4052899917996	NOXLITE® LED HP Floodlight 23W white	1.600	23	3.000	up to 30.000
4052899905603	NOXLITE® LED HP Floodlight 23W gray	1.600	23	3.000	up to 30.000
4052899918009	NOXLITE® LED HP Floodlight 40W white	2.800	40	3.000	up to 30.000
4052899905610	NOXLITE® LED HP Floodlight 40W gray	2.800	40	3.000	up to 30.000
AquaLED® 2 S, M					
 4008321988775	AquaLED® 2 S	60	1.5	3.000	up to 35.000
4008321988782	AquaLED® 2 S	60	1.5	4.000	up to 35.000
4008321988836	AquaLED® 2 M	130	2.8	3.000	up to 35.000
4008321988843	AquaLED® 2 M	130	2.8	4.000	up to 35.000

¹ provisional technical data-sheet

² L70/B50

³ available starting August 2014